

Limited Warranty

We warrant to the original purchaser of the Rack-Strap® Ladder Lock manufactured by us, to be free from defects in material and workmanship under normal use and service. Our obligation under this warranty shall be limited to the repair or exchange of any part or parts which may thus prove defective under normal use and service within thirty (30) days from date of purchase by the original purchaser, and which our examination shall disclose, to our satisfaction, to be thus defective.

THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND OF ALL OTHER OBLIGATIONS OR LIABILITIES ON OUR PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY OTHER PERSON TO ASSUME FOR US, ANY OTHER LIABILITY IN CONNECTION WITH THE SALE OF THIS RACK-STRAP® LADDER LOCK OR ANY PART THEREOF WHICH HAS BEEN SUBJECT TO ACCIDENT, NEGLIGENCE, ALTERATION, ABUSE, OR MISUSE. WE MAKE NO WARRANTIES WHATSOEVER IN RESPECT TO ACCESSORIES OR PARTS NOT SUPPLIED BY US. THE TERM "ORIGINAL PURCHASER", AS USED IN THIS WARRANTY, SHALL BE DEEMED TO MEAN THAT PERSON TO WHOM THE RACK-STRAP® LADDER LOCK WAS ORIGINALLY SOLD. THIS WARRANTY SHALL APPLY ONLY WITHIN THE BOUNDARIES OF THE CONTINENTAL UNITED STATES OF AMERICA.

RACK-STRAP® INC.

www.RackStrap.com

2750 INDUSTRIAL AVENUE
HUBBARD, OR 97032

800-841-5790
Ph: 503-982-1920
Fax: 503-982-7022

Cautions

The Rack-Strap® Ladder Lock was designed to be a superior theft deterrent system for ladders. However, preventative maintenance must be performed and common sense must be used. The following is a partial list of considerations which may help with your use of the Rack-Strap® Ladder Lock.

- Inspect the entire system frequently.
- Check mounting welds and/or bolts frequently. Tighten bolts when necessary.
- Use only replacement parts manufactured by Rack-Strap®, Inc.
- Keep lock cover in the down position when not locking or unlocking the unit to keep housing and lock clear of all debris and in good working condition. Occasional application of a light lubricant to lock will contribute to proper lock performance.
- Never mount Ladder Locks on the recessed portion of forklift side loading racks.
- Engage the Ladder Lock only as illustrated.
- Ladder Lock may increase the height of your vehicle.
- Never position Ladder Lock arm outward from vehicle.
- Ladder Lock is a theft deterrent device. It is not intended for use as a tie-down. Proper tie-downs, such as the Rack-Strap®, should be used in combination with the Ladder Lock.

RACK-STRAP® Ladder Lock

www.RackStrap.com

